




# TECHNICAL DATASHEET

**EPS** EXPANDED POLYSTYRENE  
INSULATION



## Warm-R SD E Grey

**Dimensions:** 2400 x 1200mm, 1800 x 1200mm  
**Profile:** Straight Edge

### 1. Products & Units

Essential Characteristics	Performance	Test Standard
Thermal Conductivity	$\lambda_D = 0.031 \text{ W/mK}$	EN 12667
Density	$15\text{kg/m}^3 \pm 2$	-
Reaction to Fire	Euroclass E	EN 13501-1
Thickness	T2	EN 823
Length	L2	EN 822
Width	W2	EN 822
Squareness	S2	EN 824
Flatness	P3	EN 825
Compressive Strength	CS (10/Y) 70	EN 826
Dimensional Stability	DS (70,90) 1	EN 1604

**ISO 9001** Quality Management Systems  
**ISO 14001** Environmental Management Systems

\*Product available in other dimensions subject to a minimum order quantity and lead time

**Unilin Insulation Ireland Ltd**  
Liscarton Industrial Estate, Kells Road, Navan, Co. Meath Ireland, C15 NP79

**T** +353 (0)46 906 6000  
**F** +353 (0)46 906 6090  
**E** info.ui@unilin.com

